

Article Number: 151-30702



Description: Cable Tie Mount, .86" x .62", .25" Hole Dia, .31" Max Tie

Width, PA66, Black, 1000/pkg

| Base Data | | |
|-----------------------------|-------------------------------------|--|
| | | |
| | Local Order Number | CTM40M4 |
| | Туре | CTM4 |
| | Color | Black (BK) |
| | Features and Benefits | Designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. Secures with a single screw providing quick installation. |
| | Quantity Per | bag |
| | Product Description | HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw. |
| | Short Description | Cable Tie Mount, .86" x .62", .25" Hole Dia, .31" Max Tie Width, PA66, Black, 1000/pkg |
| Product Dimensions | | |
| | Length L (Imperial) | 0.86" |
| | Length L (Metric) | 21.8mm |
| | Fixation Method | Screw Mounting and Rivet |
| | Width W (Imperial) | 0.62" |
| | Width W (Metric) | 15.8mm |
| | Cable Tie Width Max. (Imperial) | 0.31" |
| | Cable Tie Width Max. (Metric) | 7.9mm |
| | Height H (Imperial) | 0.37" |
| | Height H (Metric) | 9.4mm |
| | Mounting Hole Diameter D (Imperial) | 0.25" |
| | Mounting Hole Diameter D (Metric) | 6.4 mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 (PA66) |

generated on: 4/28/2017

151-30702



| Material and Specifications | Material Shortcut | PA66 |
|--------------------------------|-------------------------------|----------------------------------|
| | Flammability | UL 94 V2 |
| | Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| | ROHS Compliant | Yes |
| | Certification/Specification | UL62275 |
| | UL Recognized (US and Canada) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 1000 |
| | Package Quantity (Metric) | 1000 |
| | Customs Number(Schedule B) | 3926909987 |

generated on: 4/28/2017